Clamshell Credential for BLE Reader

ACSC2

clamshell credential for BLE reader

Features

- Up to 2.25in read range
- High-Security Encryption Technology
- Frequency 13.56MHz
- Fraudulent Data Detection Solution
- Lifetime warranty
- Pack quantity: 25 cards
- NDAA Compliant*



Technical Specification	
Technology	Smartcard
Frequency	13.56 MHz
Operation	Passive (no battery)
Type	Clamshell-style card
Formats	Wiegand 26-bit
Material	ABS housing, PC sticker
Color	White
Slot Punch	Standard, vertical slot
Marking	Date code and ID
Read Range	Up to 2.25in (57mm)
Outputs	Multi-application
Warranty	Lifetime warranty
Dimensions	2.1" W x 3.4" H x .07" D (54mm x 86mm x 1.8mm)
Weight	0.35oz (10g)
Operating Temperature	-40°F to 158°F (-35°C to 70°C)
Humidity	0-95% non-condensing
Memory	2K memory standard
ISO Standards	ISO 14443-A
Technologies Supported	MIFARE® DESFire EV2
Supporting Readers	ACSR35L

NDAA COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/19/22