

Features

- **High Definition Display:** The backup camera monitor adopts 10.1 inch TFT LCD large screen with 16:9 display ratio and 1024 x 600 (analog) / 1920 x 1080 (VGA) high definition resolution, providing clear and clean image.
- **Considerate Design:** Backup monitor comes with sun visor to see more clearly on sunny day. Supplied with adhesive sticker in the bottom for sticking, 180 degree adjustable.
- **V1 Video Input:** MVR.
- **High Compatibility:** Reversing monitor supports.
- **Universal Smart Chipset:** Compatible with both PAL and NTSC video systems. Automatically power up screen when needed, prevent accidents to save you from unnecessary loss or troubles while in reverse by avoiding children, traffic, pedestrians, toys and pets."



Specification

Material	ABS, METAL
Rated Working Voltage	12V/24V DC, power on to start
Acceptable Voltage Range	9-35V DC
Display	HD screen
Display Ratio	16:09
Resolution	1024 x 600 (analog) / 1920 x 1080 (VGA)
Contrast	650:01:00
Brightness	600cd/m2
Response Time	5ms
Display Color	16.7M
Video Format	PAL/NTSC
Video Input	1 way aviation head male / VGA
Language Menu	OSD menu
Viewing Angle	U: 55 / D: 55, R/L: 60
Working Temperature	-20°C-70°C