DTK-UPS Series

Line Interactive Uninterruptible Power Supplies





DITEK's DTK-UPS Series 600VA and 1000VA models are designed to provide clean and stable power to connected equipment utilizing the built-in AVR stabilizer, while its embedded microprocessor control guarantees exceptional reliability. All outlets on each model provide backup power to critical equipment.

PRODUCT FEATURES

- Compliant to U.S. DOE Energy Conservation Standard efficiency requirements (Jan 2022)
- Provides a comprehensive backup power solution in a small, economic package
- Built-in protection for an Ethernet circuit
- Embedded microprocessor control guarantees exceptional reliability
- Built-in boost and buck AVR for voltage stabilization
- Touch screen LCD to rotate through display information
- Auto-restart while AC is recovering
- Off-mode charging
- Cold start function
- USB connection for software download

APPLICATIONS

- Home and Office Workstations
- POS Terminals
- Small Phone Systems
- Home Theater Systems

DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345
Diteksurgeprotection.com • SPS-100019-001 Rev 6 05/26

Every precaution has been taken to ensure that this is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

DTK-UPS Series

Line Interactive Uninterruptible Power Supplies

TECHNICAL SPECIFICATIONS		
Part Number:	**DTK-UPS600**	**DTK-UPS1000**
Capacity:	600VA / 360W	1000VA / 600W
INPUT		
Input Voltage:	110/120Vac	
Voltage Range:	81-145Vac	
Frequency Range:	50/60Hz (Auto-sensing)	
OUTPUT		
Output Voltage:	110/120Vac	
AC Voltage Regulation:	Battery mode: +/- 10%	
Frequency Range:	Battery mode: 50Hz or 60Hz +/- 1Hz	
Transfer Time:	2ms - 6ms	
Waveform (Battery Mode):	Simulated sinewave	
Number of Outlets:	6 (UPS)	8 (UPS)
BATTERY		
Battery Type & Quantity:	12Vdc / 7Ah x 1	12Vdc / 7Ah x 2
Battery Run Time:	19 minutes @ 25% load	21 minutes @ 25% load
Typical Recharge Time:	4-6 hours recover to 90% capacity	
PROTECTION & INDICATORS		
Full Protection:	Battery Mode: Every 10 seconds Low Battery: Every second Overload: Every 0.5 seconds Fault: Continuous	
LCD:	Input Voltage, Output Voltage, Battery, Load	
Alarm Sounding:		
PHYSICAL & ENVIRONMENTAL		
Dimensions:	11.0 in. L x 4.0 in. W x 5.6 in. H (279 mm x 101 mm x 142 mm)	12.6 in. H x 5.1 in. W x 7.2 in. H (320 mm x 130 mm x 182 mm)
Weight:	10 lbs. (4.54 kg)	18.5 lbs. (8.39 kg)
Humidity:	0-90% relative humidity @ 0-40°C (non-condensing)	
Noise Level:	Less than 40dB	
SAFETY STANDARDS & CERTIFICATIONS		
Certifications:	UL 1778-2014 CSA C22.2 No.107.3-2014	
U.S. DOE Compliance:	Yes	
Overall Efficiency:	> 98.4%	

DITEK Surge Protection, Largo, FL 33771 • Sales: 800-753-2345
Diteksurgeprotection.com • SPS-100019-001 Rev 6 05/26

9001:2015

Every precaution has been taken to ensure that this is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.