

IXW-PBXA

IP PBX Adaptor

The IXW-PBXA is a Grandstream IP PBX adaptor that integrates with IX|IXG Series stations, allowing the stations to call to an outside telephone line.

This adaptor is intended for sites where IP PBX features are required, but a full or compatible system is not available.



- Supports up to 500 registered SIP devices and up to 75 concurrent calls

- Dual Gigabit network ports with integrated PoE+

- Built-in call recording server; recordings can be accessed via web interface

- Built-in call detail records for tracking phone usage

- Supports any SIP video endpoint

- Supports voice mail

- Supports call queue for call volume management

Power Source 12V DC, 1.5A (supplied)

Video Codecs H.264, H.263, H.263+, H.265, VP8

Network Interface Three self-adaptive Gigabit with integrated PoE+ (IEEE 802.3at)

Ports 2 PSTN FXO, 2 analog FXS

Protocols TCP/UDP/IP, RTP/RTCP, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, PPPoE, SIP, STUN, SRTP, TLS, LDAP, HDLC, HDLC-ETH, PPP, IPv6, OpenVPN®

Encryption SRTP, TLS, HTTPS, SSH

Operating Temp 32°~113°F (0°~45°C)

Dimensions	1 1/8 in H	10 5/8 in W	7 in D
	28.6 mm H	269.9 mm W	177.8 mm D