speco technologies®

500W High Efficiency 70V Power Amplifier

P500A 500W RMS power amplifier

Features

- Single speaker output works with either 70V and 8 Ohm speakers
- Auxiliary inputs and outputs to “daisy-chain” amplifiers
- Class D amplification
- Built-in rack mount





rear of unit

Specifications

RMS Output Power	500W
Max. Output Power	1000W
AC Power Consumption	<720W
Power Supply	AC 110V-120V, 50/60Hz
Zones	1
Speaker Outputs	8 Ohms, 70V
Other Outputs	Aux (XLR)
Inputs	1 x Aux (XLR or Terminal)
Frequency Response	70Hz ~ 18KHz (±3dB)
Tone Control	n/a
THD	Less than 0.1% @1KHz
Signal/Noise Ratio	>90dB
Controls	Master Volume
Telephone	n/a
Indicators	Power, power level
Dimensions	19” (W) x 3.46” (H) x 15.75” (D)
Weight	18 lbs.
Includes	Built-in Rack Mount
Listings	CE, FCC, RoHS

NDAA COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/24/22